

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : VANASOLVENT
 Product code : UNIM040
 Type of product : Solvents
 Product group : Blend

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use, Professional use
 Industrial/Professional use spec : For professional use only
 Industrial
 Function or use category : Solvents

Title	Use descriptors
	SU3, PC35, PROC5, ERC2

Full text of use descriptors: see section 16

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

UNIMARINE SERVICES INC.
 60 MARKET SQUARE
 PO BOX 364
 BELIZE CITY
 T +35725331054
info@unimarine-services.com

1.4. Emergency telephone number

Emergency number : +35725331054

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 3 H226
 Serious eye damage/eye irritation, Category 2 H319
 Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation H335
 Specific target organ toxicity — Single exposure, Category 3, Narcosis H336
 Aspiration hazard, Category 1 H304
 Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Flammable liquid and vapour. May cause drowsiness or dizziness. May cause respiratory irritation. Causes serious eye irritation. May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



VANASOLVENT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Signal word (CLP)	: Danger
Hazardous ingredients	: Kerosine : solvent naphta heavy aromatic
Hazard statements (CLP)	: H226 - Flammable liquid and vapour H304 - May be fatal if swallowed and enters airways H319 - Causes serious eye irritation H335 - May cause respiratory irritation H336 - May cause drowsiness or dizziness H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (CLP)	: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking P233 - Keep container tightly closed P240 - Ground/bond container and receiving equipment P241 - Use explosion-proof Material equipment P261 - Avoid breathing vapours P264 - Wash hands thoroughly after handling
EUH-statements	: EUH066 - Repeated exposure may cause skin dryness or cracking

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Naphtha (petroleum), hydrodesulfurized heavy	(EC No) 265-185-4 (CAS-No) 64742-82-1	30 - 60	R10	Flam. Liq. 3, H226 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Full text of R- and H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: If medical advice is needed, have product container or label at hand.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May cause drowsiness or dizziness.
Symptoms/injuries after inhalation	: May cause respiratory irritation.
Symptoms/injuries after skin contact	: Contact during a long period may cause light irritation.
Symptoms/injuries after eye contact	: Eye irritation.
Symptoms/injuries after ingestion	: Risk of lung oedema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Extinguishing media

Suitable extinguishing media : carbon dioxide (CO₂), foam, water spray, powder.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapour.

VANASOLVENT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Hazardous decomposition products in case of fire : Carbon monoxide. fume.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area.
 Firefighting instructions : Evacuate area. Exercise caution when fighting any chemical fire. Prevent fire fighting water from entering the environment.
 Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : No flames, no sparks. Eliminate all sources of ignition.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
 Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
 Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Avoid breathing vapours.
 Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
 Storage conditions : Store in a well-ventilated place. Keep cool. Protect from sunlight. Keep container tightly closed.
 Incompatible products : Oxidizing agent.
 Incompatible materials : Butyl rubber. Ethylene-Propylene rubber (EPDM) /. Natural rubber. Polystyrene.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

TLV (TWA) (Naphtha (petroleum), hydrodesulfurized heavy) 275 mg/m³ ()

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

protective gloves

Eye protection:

Safety glasses

VANASOLVENT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear.
Colour	: Colorless.
Odour	: Smells of Hydrocarbon.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: > 62 °C
Auto-ignition temperature	: 220°C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: 0,85 g/cm3
Relative density	: No data available
Density	: 0,82 - 0,88
Solubility	: Soluble in water.
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None under normal conditions.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

FOT DUAL PURPOSE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acute toxicity (dermal) : Not classified
 Acute toxicity (inhalation) : Not classified

Kerosine : solvent naphta	
LD50 oral rat	3492 mg/m ³ OESO 401
LD50 dermal rabbit	> 3160 mg/kg OESO 402
LC50 inhalation rat (ppm)	> 6193 ppm/4h OESO 403

Skin corrosion/irritation : Not classified
 Serious eye damage/irritation : Causes serious eye irritation.
 Respiratory or skin sensitisation : Not classified
 Germ cell mutagenicity : Not classified
 Carcinogenicity : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects.
 Acute aquatic toxicity : Not classified
 Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Kerosine : solvent naphta	
LC50 fish 1	2 - 5 mg/l 96 h - Oncorhynchus mykiss
EC50 Daphnia 1	3 - 10 mg/l 48 h - Daphnia magna

12.2. Persistence and degradability

VANASOLVENT	
Persistence and degradability	May cause long-term adverse effects in the environment. This surfactant complies with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

Kerosine : solvent naphta heavy aromatic	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste) : Disposal must be done according to official regulations.

VANASOLVENT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR)	: 1268
UN-No. (IMDG)	: 1268
UN-No. (IATA)	: 1268
UN-No. (ADN)	: 1268
UN-No. (RID)	: 1268

14.2. UN proper shipping name

Proper Shipping Name (ADR)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IMDG)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (IATA)	: Not applicable
Proper Shipping Name (ADN)	: PETROLEUM DISTILLATES, N.O.S.
Proper Shipping Name (RID)	: PETROLEUM DISTILLATES, N.O.S.
Transport document description (ADR)	: UN 1268 PETROLEUM DISTILLATES, N.O.S. (Solvent nafta), 3, III, (D/E), ENVIRONMENTALLY HAZARDOUS
Transport document description (IMDG)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS
Transport document description (IATA)	: UN 1268 , 3, ENVIRONMENTALLY HAZARDOUS
Transport document description (ADN)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS
Transport document description (RID)	: UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR)	: 3
Danger labels (ADR)	: 3



IMDG

Transport hazard class(es) (IMDG)	: 3
Danger labels (IMDG)	: 3



IATA

Transport hazard class(es) (IATA)	: 3
Danger labels (IATA)	: 3



ADN

Transport hazard class(es) (ADN)	: 3
Danger labels (ADN)	: 3



VANASOLVENT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

RID

Transport hazard class(es) (RID) : 3
 Danger labels (RID) : 3



14.4. Packing group

Packing group (ADR) : III
 Packing group (IMDG) : III
 Packing group (IATA) : Not applicable
 Packing group (ADN) : III
 Packing group (RID) : III


14.5. Environmental hazards

Dangerous for the environment : Yes
 Marine pollutant : Yes
 Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

Classification code (ADR) : F1
 Special provisions (ADR) : 363
 Limited quantities (ADR) : 5l
 Excepted quantities (ADR) : E1
 Packing instructions (ADR) : P001, IBC03, LP01, R001
 Mixed packing provisions (ADR) : MP19
 Portable tank and bulk container instructions (ADR) : T4
 Portable tank and bulk container special provisions (ADR) : TP1, TP29
 Tank code (ADR) : LGBF
 Vehicle for tank carriage : FL
 Transport category (ADR) : 3
 Special provisions for carriage - Packages (ADR) : V12
 Special provisions for carriage - Operation (ADR) : S2
 Hazard identification number (Kemler No.) : 30
 Orange plates :



Tunnel restriction code (ADR) : D/E
 EAC code : 3YE

- Transport by sea

Special provisions (IMDG) : 223, 363, 955
 Limited quantities (IMDG) : 5 L
 Excepted quantities (IMDG) : E1
 Packing instructions (IMDG) : P001, LP01
 IBC packing instructions (IMDG) : IBC03
 Tank instructions (IMDG) : T4
 Tank special provisions (IMDG) : TP1, TP29
 EmS-No. (Fire) : F-E
 EmS-No. (Spillage) : S-E

FOT DUAL PURPOSE

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Stowage category (IMDG) : A
 Properties and observations (IMDG) : Immiscible with water.
 MFAG-No : 128

- Air transport

No data available

- Inland waterway transport

Classification code (ADN) : F1
 Special provisions (ADN) : 363
 Limited quantities (ADN) : 5 L
 Excepted quantities (ADN) : E1
 Carriage permitted (ADN) : T
 Equipment required (ADN) : PP, EX, A
 Ventilation (ADN) : VE01
 Number of blue cones/lights (ADN) : 0

- Rail transport

Classification code (RID) : F1
 Special provisions (RID) : 363
 Limited quantities (RID) : 5L
 Excepted quantities (RID) : E1
 Packing instructions (RID) : P001, IBC03, LP01, R001
 Mixed packing provisions (RID) : MP19
 Portable tank and bulk container instructions (RID) : T4
 Portable tank and bulk container special provisions (RID) : TP1, TP29
 Tank codes for RID tanks (RID) : LGBF
 Transport category (RID) : 3
 Special provisions for carriage – Packages (RID) : W12
 Colis express (express parcels) (RID) : CE4
 Hazard identification number (RID) : 30

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions
 Contains no substance on the REACH candidate list
 Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) nwg, Non-hazardous to water (Classification according to VwVwS, Annex 4)
 12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
 SZW-lijst van mutagene stoffen : None of the components are listed
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : None of the components are listed
 NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : None of the components are listed

VANASOLVENT

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Denmark

Classification remarks : Emergency management guidelines for the storage of flammable liquids must be followed
 Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-statements:

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Liq. 3	Flammable liquids, Category 3
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H226	Flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H411	Toxic to aquatic life with long lasting effects
EUH066	Repeated exposure may cause skin dryness or cracking
R10	Flammable
R41	Risk of serious damage to eyes
Xi	Irritant
ERC2	Formulation of preparations
PC35	Washing and cleaning products (including solvent based products)
PROC5	Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
SU3	Industrial uses: Uses of substances as such or in preparations* at industrial sites

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product