

MARISOL

APPLICATIONS

- Cleaning and disinfection of Refrigerated Rooms
- Cleaning of soft and light, non oxidized vegetable and animal oil residues from tank surfaces
- Suitable for use on most tank coatings including aluminum, zinc alloy and other light metal alloys
- Cleaning of steam sides of condensers
- Cleaning of oil and grease residues in heat exchangers, pre-heaters etc.

ADVANTAGES

- Light detergent power
- Effective for cleaning and disinfection of reefer cargo holds and storage spaces, deep freezers.
- Leaves grease-free surfaces
- Rapid penetration
- Rapid rinsing
- Can be used on ferrous metals, aluminum, tin, zinc, copper and their alloys
- Saves time and reduces labor costs
- Non corrosive
- Non caustic
- Non flammable

DIRECTIONS FOR USE - PRODUCT DOSAGE

HIGH PRESSURE WORK

For high-pressure work allow *MARISOL* to penetrate for 3 to 5 minutes before washing off to prevent *MARISOL* from drying on the surface to be cleaned and forming edges; keep it damp. Cleaning effect is greatly increased by working with warm water.

For high-pressure work dilute 1 Ltr *MARISOL* wit 5 Ltr of water.

TANK CLEANING

- Cleaning of tanks should, if possible, be carried out immediately after discharge of contents.
- *MARISOL* should be mixed in a 2% to 5% solution with fresh water and applied at a temperature above 60°C where possible. Use approx. 0,5 Ltr per square meter in case of 1 mm thickness of deposit.
- For solutions with salt water we recommend dosage amount should be 1½ times greater than the amount required with fresh water.
- Apply by circulation, spray, steam or soak. For fast and efficient cleaning best results are obtained by using fixed and portable tank cleaning machines such as Butterworth or similar.
- Flush out tanks after final cleaning, preferably with fresh water.

Continued on page 2

Code: 161161416



MARISOL

Medium duty water-based cleaning agent containing alkaline salts and surfactants.

- Reefer cleaning and disinfection of reefer cargo holds
- Designed for high pressure cleaning machines
- Non-caustic alkaline cleaner
- Tank cleaning of vegetable, animal and mineral oil residues
- Degreasing of heat exchangers, condensers, etc.

PRODUCT CHARACTERISTICS

Appearance: clear liquid
Specific gravity: 1 (20°C)
pH 1% solution: 10
Flash point: none

IMO Class: not regulated
UN Number: not regulated
ADR: not regulated



This information is not to be taken as a warranty or representation for which we assume legal responsibility, nor as permission, inducement or recommendation to practice any patented invention without a licence. The information is offered solely for your consideration, investigation and verification.

CLEANING CONDENSERS OR HEAT EXCHANGERS

- Prepare a 5% solution of *MARISOL* with fresh water.
- Apply by circulation for 24 hours, or by filling condenser or heat exchanger approx. half full, heating and agitating by steam lance or auxiliary steam line. A temperature of 60°C to 90°C should be maintained during cleaning process.
- Drain and thoroughly flush with fresh water.

NATURE OF SPECIAL RISKS AND SAFETY ADVICE

In accordance with the latest EEC Council directives this product is subjected to:

R36/38 : Irritating to the eyes and to the skin

S2 : Keep out of reach of children

S24/25 : Avoid contact with skin and eyes

S36/37/39 : Wear suitable protective clothing, gloves and eye / face protection