

APPLICATION

CEMENT REMOVER is used for removing cement residues from all common metal surfaces. It must not be used on zinc, aluminum, galvanized materials and stainless steel.

DIRECTIONS FOR USE

Apply *CEMENT REMOVER* with brush to surfaces to be cleaned.

- Use undiluted for hard cement deposits on the surfaces.
- Use diluted in solution of 1 part *CEMENT REMOVER* to 5 - 10 parts water, depending on the thickness of the cement layer.
- Rinse thoroughly with water after 10 to 15 minutes after application.

NATURE OF SPECIAL RISKS AND SAFETY ADVICE

In accordance with the latest EEC Council directives this product is subjected to:

- R34 : Causes burns
R37 : Irritating to respiratory system
S2 : Keep out of reach of children
S26 : In case of contact with eyes, rinse immediately with plenty of water and seek medical advice
S28 : After contact with skin, wash immediately with plenty of water and seek medical advice
S36/37/39 : Wear suitable protective clothing, gloves and eye / face protection
S45 : In case of accident or if you feel unwell, seek medical advice immediately (show the label if possible)



CEMENT REMOVER

Strong acid compound specially designed for the removal of cement deposits from most common surfaces

- Fast and efficient cement removal
- Inhibited against attack on ferrous metals
- Forms protective coating on steel surfaces to which paint adheres readily
- Biodegradable and non flammable

PRODUCT CHARACTERISTICS

Appearance:	clear liquid, yellowish or red
Corrosive action:	inhibited against attack on ferrous metals
Specific gravity:	1,1 (20°C)
Flash point:	none
pH:	pH<1
IMO Class:	8 / II
UN Number:	1789
ADR:	8.5b)

UNIservice

UNIClean

UNIGas

UNImarine
s a f e t y